

<b>REPORT DOCUMENTATION PAGE</b>			Form Approved OMB NO. 0704-0188		
<p>The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA, 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.</p> <p>PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.</p>					
1. REPORT DATE (DD-MM-YYYY) 05-01-2016		2. REPORT TYPE Final Report		3. DATES COVERED (From - To) 28-Aug-2012 - 27-Aug-2013	
4. TITLE AND SUBTITLE Final Report: A Computing Platform for Parallel Sparse Matrix Computations			5a. CONTRACT NUMBER W911NF-12-1-0447		
			5b. GRANT NUMBER		
			5c. PROGRAM ELEMENT NUMBER 611103		
6. AUTHORS Ahmed H. Sameh, Alicia Klinvex, Yao Zhu			5d. PROJECT NUMBER		
			5e. TASK NUMBER		
			5f. WORK UNIT NUMBER		
7. PERFORMING ORGANIZATION NAMES AND ADDRESSES Purdue University 155 S. Grant Street  West Lafayette, IN 47907 -2114			8. PERFORMING ORGANIZATION REPORT NUMBER		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS (ES) U.S. Army Research Office P.O. Box 12211 Research Triangle Park, NC 27709-2211			10. SPONSOR/MONITOR'S ACRONYM(S) ARO		
			11. SPONSOR/MONITOR'S REPORT NUMBER(S) 61443-CS-RIP.5		
12. DISTRIBUTION AVAILABILITY STATEMENT Approved for Public Release; Distribution Unlimited					
13. SUPPLEMENTARY NOTES The views, opinions and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy or decision, unless so designated by other documentation.					
14. ABSTRACT This grant enabled the purchase of an Intel multiprocessor consisting of eight multicore nodes interconnected via an infiniband. Each node contains 24 cores. This parallel computing platform has been used by my research group in the early stages of developing large sparse linear system and symmetric eigenvalue problem solvers (ARO grant W911NF-07-R-0003-04) that are suitable for parallel architectures containing hundreds of multicore nodes (thousands of cores). Once our parallel solvers obtain the correct solutions, and perform properly on this 8-node platform, the codes are ported to much larger parallel computing platforms at the Intel Corporation. Type Bb D.					
15. SUBJECT TERMS large sparse linear system solvers, large sparse symmetric eigenvalue problem solvers, parallel programming					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	15. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON
a. REPORT UU	b. ABSTRACT UU	c. THIS PAGE UU			Ahmed Sameh
					19b. TELEPHONE NUMBER 765-494-1559



## Report Title

Final Report: A Computing Platform for Parallel Sparse Matrix Computations

### ABSTRACT

This grant enabled the purchase of an Intel multiprocessor consisting of eight multicore nodes interconnected via an infiniband. Each node contains 24 cores. This parallel computing platform has been used by my research group in the early stages of developing large sparse linear system and symmetric eigenvalue problem solvers (ARO grant W911NF-07-R-0003-04) that are suitable for parallel architectures containing hundreds of multicore nodes (thousands of cores). Once our parallel solvers obtain the correct solutions, and perform properly on this 8-node platform, the codes are ported to much larger parallel computing platforms at the Intel Corporation. Two Ph.D. dissertations have resulted from the above grant (awarded by Dr. Myers), and this DURIP grant (awarded by Dr. Coyle).

---

**Enter List of papers submitted or published that acknowledge ARO support from the start of the project to the date of this printing. List the papers, including journal references, in the following categories:**

**(a) Papers published in peer-reviewed journals (N/A for none)**

Received

Paper

**TOTAL:**

**Number of Papers published in peer-reviewed journals:**

---

**(b) Papers published in non-peer-reviewed journals (N/A for none)**

Received

Paper

**TOTAL:**

**Number of Papers published in non peer-reviewed journals:**

---

**(c) Presentations**

Number of Presentations: 3.00

---

**Non Peer-Reviewed Conference Proceeding publications (other than abstracts):**

Received      Paper

**TOTAL:**

Number of Non Peer-Reviewed Conference Proceeding publications (other than abstracts):

---

**Peer-Reviewed Conference Proceeding publications (other than abstracts):**

Received      Paper

**TOTAL:**

Number of Peer-Reviewed Conference Proceeding publications (other than abstracts):

---

**(d) Manuscripts**

Received      Paper

01/05/2016    2.00    Yao Zhu, Ahmed H. Sameh. SPIKE+: A family of parallel hybrid sparse linear system solvers, Journal of Computational and Applied Mathematics (05 2015)

**TOTAL:      1**

Number of Manuscripts:

Books

Received      Book

**TOTAL:**

Received      Book Chapter

01/05/2016    1.00    Yao Zhu, Ahmed H. Sameh. How to generate effective block Jacobi preconditioners for solving large sparse linear systems, Yet to be published: Birkhauser, (02 2016)

**TOTAL:      1**

Patents Submitted

Patents Awarded

Awards

Graduate Students

<u>NAME</u>	<u>PERCENT SUPPORTED</u>	<u>Discipline</u>
Yao Zhu	0.50	
Alicia Klinvex	0.10	
<b>FTE Equivalent:</b>	<b>0.60</b>	
<b>Total Number:</b>	<b>2</b>	

### Names of Post Doctorates

NAME

PERCENT SUPPORTED

**FTE Equivalent:**

**Total Number:**

### Names of Faculty Supported

NAME

PERCENT SUPPORTED

National Academy Member

Ahmed H. Sameh

0.10

**FTE Equivalent:**

**0.10**

**Total Number:**

**1**

### Names of Under Graduate students supported

NAME

PERCENT SUPPORTED

**FTE Equivalent:**

**Total Number:**

### Student Metrics

This section only applies to graduating undergraduates supported by this agreement in this reporting period

The number of undergraduates funded by this agreement who graduated during this period: ..... 0.00

The number of undergraduates funded by this agreement who graduated during this period with a degree in science, mathematics, engineering, or technology fields:..... 0.00

The number of undergraduates funded by your agreement who graduated during this period and will continue to pursue a graduate or Ph.D. degree in science, mathematics, engineering, or technology fields:..... 0.00

Number of graduating undergraduates who achieved a 3.5 GPA to 4.0 (4.0 max scale):..... 0.00

Number of graduating undergraduates funded by a DoD funded Center of Excellence grant for Education, Research and Engineering:..... 0.00

The number of undergraduates funded by your agreement who graduated during this period and intend to work for the Department of Defense ..... 0.00

The number of undergraduates funded by your agreement who graduated during this period and will receive scholarships or fellowships for further studies in science, mathematics, engineering or technology fields:..... 0.00

### Names of Personnel receiving masters degrees

NAME

**Total Number:**

### Names of personnel receiving PHDs

NAME

Yao Zhu

Alicia Klinvex

**Total Number:**

**2**

---

### Names of other research staff

<u>NAME</u>	<u>PERCENT SUPPORTED</u>
<b>FTE Equivalent:</b>	
<b>Total Number:</b>	

---

### Sub Contractors (DD882)

### Inventions (DD882)

### Scientific Progress

Two classes of parallel solvers have been developed. The first is a family of parallel sparse linear system solvers -- the PSPIKE family (Spike/Pardiso hybrid solvers). The second is a family of Trace Minimization eigensolvers for the symmetric standard and generalized eigenvalue problems. Both classes of solvers proved to be competitive with existing solvers in being more robust and more scalable on parallel architectures with superior speeds. In particular the TraceMin eigensolvers developed through these two ARO grants have been adopted by the DOE Trilinos project at Sandia National Laboratories.

### Technology Transfer

*TraceMIN: a scalable parallel  
algorithm for large sparse symmetric  
eigenvalue problems*

*Alicia Klinvex*

*Sandia National Labs.*

*Ahmed H. Sameh*

*Computer Science, Purdue University*

*Support: ARO, Intel, NSF*

*St Girons: June 27 – July 2; 2015*



# *Symmetric Generalized Eigenvalue Problem*

$$Ax = \lambda Bx$$

*A is sparse and symmetric*

*B is sparse and s.p.d.*

*Obtain the  $p$  eigenvalues closest to 0 and their corresponding eigenvectors,  $p \ll n$*

## The Trace minimization scheme

$$\min_{Y^T B Y = I_p} \operatorname{tr}(Y^T A Y) = \sum_{i=1}^p \lambda_i$$

$$\lambda_1 \leq \lambda_2 \leq \cdots \leq \lambda_p < \lambda_{p+1} \leq \cdots \leq \lambda_n$$

$$Y \in R^{n \times p} \quad ; \quad p \ll n.$$

*A.S. & J. Wisniewski: SINUM, 1982*

*A.S. & Z. Tong: J. Comp. Appl. Math., 2000.*

## *Extensions of this optimization problem for definite matrix pair*

- *B: indefinite nonsingular*
  - *Kobac-Striko and K. Veselic (1995)*
- *B: indefinite singular*
  - *Liang, Li, and Z. Bai*

*A and B are called “definite pair” if there  
exists a scalar  $\mu$  such that  $(A - \mu B)$   
is s.p.d, or s.p.s.d*

*solve*

$$\begin{pmatrix} A & BY_k \\ Y_k^T B & O \end{pmatrix} \begin{pmatrix} \Delta_k \\ L_k \end{pmatrix} = \begin{pmatrix} AY_k \\ O \end{pmatrix} \quad *$$

*or*

$$\begin{pmatrix} A & BY_k \\ Y_k^T B & O \end{pmatrix} \begin{pmatrix} Y_k - \Delta_k \\ -L_k \end{pmatrix} = \begin{pmatrix} O \\ I_p \end{pmatrix} \quad **$$

- $(Y_k - \Delta_k)$  is used to generate  $Y_{k+1}$
- $\text{tr}(Y_{k+1} A Y_{k+1}) \leq \text{tr}(Y_k A Y_k)$
- Different schemes (direct/iterative) for solving (\*) or (\*\*)
- TraceMIN **does not** require low relative residuals in solving (\*) or (\*\*)

*a) Using a direct sparse linear system solver (Pardiso)*

- *Solve*

$$AZ_k = BY_k \quad \text{for } Z_k$$

- *Solve*

$$\begin{pmatrix} I & Z_k \\ Y_k^T B & O \end{pmatrix} \begin{pmatrix} Y_k - \Delta_k \\ -L \end{pmatrix} = \begin{pmatrix} O \\ I_p \end{pmatrix}$$

$$\text{for } (Y_k - \Delta_k)$$

*b) Use a Krylov subspace method to solve*

$$(I - P_k)A(I - P_k)\Delta_k = (I - P_k)AY_k$$

*for  $\Delta_k$*

*where*

$$P_k = BY_k(Y_k^T B^2 Y_k)^{-1} Y_k^T B.$$

*e.g. CG, or Minres; rel. res  $\leq 10^{-6}$*

*c) Solve*

$$\begin{pmatrix} A & BY \\ Y^T B & 0 \end{pmatrix} \begin{pmatrix} Y - \Delta \\ -L \end{pmatrix} = \begin{pmatrix} 0 \\ I_p \end{pmatrix}$$

*via a Krylov subspace method with the preconditioner*

$$M = \text{diag} (\hat{A}, Y^T B \hat{A}^{-1} B Y)$$

*$\hat{A}$  is an approximation of  $A$*

# TraceMIN algorithm

- Choose initial  $(n \times s)$  block  $V$ ;  $s \approx 2p$
- Repeat until convergence
  - 1. B-orthonormalize  $V$
  - 2. Form approximate eigenpairs
$$Y^T A Y = \Sigma, \quad Y^T B Y = I; \quad \Sigma = \text{diag}(\sigma_1, \sigma_2, \dots, \sigma_s)$$
  - 3.  $R = AY - BY\Sigma$ , check  $\text{norm}(r_k) / \sigma_k \leq 10^{-5}$
  - 4. Solve saddle-point problem for  $\Delta$  or  $Y - \Delta$
  - 5. update  $V = Y - \Delta$



# Convergence

- Convergence bounded by  $|\lambda_k / \lambda_{s+1}|$
- Origin shifts can lead to faster convergence

$$-(A - \mu_k B) x_k = (\lambda_k - \mu_k) x_k$$

$$-|(\lambda_k - \mu_k) / \lambda_{s+1}|$$

- If  $A$  is s.p.d, then

$$\Phi_k = (y_k - x_k)^T A (y_k - x_k)$$


is reduced asymptotically by a factor of

$$(\lambda_k / \lambda_{s+1})^2$$

# *Simultaneous Iterations & TraceMIN*

- *Simultaneous Iterations is mathematically equivalent to TraceMIN.*
- *In each step of Simultaneous Iterations, we need to solve systems of the form  $\mathbf{A} \mathbf{V} = \mathbf{B} \mathbf{Y}$ .*
- *If we solve such systems, as well as TraceMIN saddle-point problems using Minres, for example, with a modest stopping criterion, i.e.  $\text{rel. res.} \leq 0.5$ , we get vastly different behavior in reduction of the trace.*

*Minres: rel. res  $\leq 0.5$*



*$< 25$  iterations*

# *Three trace minimization schemes for the symmetric eigenvalue problem*

<i>Solver</i>	<i>TraceMIN 1982</i>	<i>Jacobi-Davidson (JD – 1996)</i>	<i>TraceMIN- Davidson (TD-2000)</i>
<i>Subspace dimension</i>	<i>constant</i>	<i>expanding</i>	<i>expanding</i>
<i>Choice of shifts</i>	<i>conservative</i>	<i>aggressive</i>	<i>conservative</i>

*How to handle expanding subspaces*

$$V := [V, \Delta]$$

*Upon restart, retain only relevant part of the subspace*

# *Performance Results: a sample*

*Codes in Trilinos framework*

*TraceMIN & TraceMIN-Davidson (TD) vs:*

*1. The DOE Trilinos Anasazi package –*

- Krylov Schur (KS) [G.W. Stewart]; (BKS) [Saad]*
- Locally Optimal Block Preconditioned Conjugate Gradient (LOBPCG), [Knyazev]*
- Riemannian Trust Region (RTR) \*\* [Baker et al]*

*2. The SLEPc package -- Jacobi-Davidson (JD) \*\**

*\*\* TraceMIN-based*

# *Robustness*

- *Obtain the 4 smallest eigenpairs of the standard eigenvalue problem:  $A x = \lambda x$*
- *Source: Tim Davis sparse matrix collection*
- *3 benchmarks for which  $A$  is symmetric positive definite*
- *1 benchmark for which  $A$  is indefinite*
- *✓: success*
- *✗: failure (no convergence or wrong multiplicity)*

# *Computing Platform*

- *Intel cluster: Endeavor*
- *Infiniband interconnection network*
- *Each node consists of two 14-core Intel processors running at 2.6 GHz*
- *64 GB per node*
- *Hybrid programming paradigm **MPI/OpenMP***

# Robustness

Matrix	<u>Type</u> <i>n</i>	TD	BKS	LOBPCG	RTR	KS	JD
Poisson	spd 64 M	✓	✓	✗	✓	✗	✗
Flan_1565	spd 1.5 M	✓	✗	✗	✓	✗	✓
Hook_1498	spd 1.5 M	✓	✗	✗	✓	✗	✓
nlpkkt240	Indef. 28 M	✓	✗	✗	✗	✗	✓
ANASAZI						SLEPc	




# $Time(\text{algorithm } X) / Time(TD)$

- 32 nodes (24 cores per node)

matrix	Type	n	TD	BKS	LOBPCG	RTR	KS	JD
Hook_1498	spd	1.5 M	1.0	✗	✗	3.3	✗	1.5

- 128 nodes (24 cores per node)

matrix	Type	n	TD	BKS	LOBPCG	RTR	KS	JD
Poisson	spd	64 M	1.0	19.7	3	1.6	✗	--
Flan_1565	spd	1.5 M	1.0	✗	✗	1.3	✗	2.1
nlpkkt240	indef	28 M	1.0	✗	✗	✗	✗	6.6



*computing the 4 smallest  
eigenpairs of nlpkkt240*

*nodes*

# *TraceMIN: multisectioning & sampling*

*(codes in Fortran 90)*

- *Multisectioning:*
  - *For obtaining a large number of interior eigenvalues and their corresponding eigenvectors*
- *Sampling:*
  - *Obtaining several eigenpairs in the neighborhood of a given number of points within the spectrum*

# *Multisectioning*

- *Using several shifts  $\alpha_j$  we can obtain that interval  $(0, \tau)$  that contains the number of eigenpairs desired.*
- *Divide the interval under consideration into many subintervals, one subinterval per node; each containing roughly the same number of eigenvalues (e.g. 20), if possible*
- *For each node  $j$ , we use our shared-memory TraceMIN eigensolver to obtain the smallest eigenpairs of  $(A - \alpha_j B) x = (\lambda - \alpha_j) B x$ .*

*With the shifts  $\alpha$ , we get saddle-point problems of the form:*


$$\begin{pmatrix} A - \alpha B & BY_k \\ Y_k^T B & O \end{pmatrix} \begin{pmatrix} Y_k - \Delta_k \\ -L_k \end{pmatrix} = \begin{pmatrix} O \\ I_p \end{pmatrix}.$$

*A sparse direct solver (Pardiso) is used to  
Obtain the factorization of the indefinite  
(1,1) block:*

$$A - \alpha B = LDL^T.$$

## *Multisectioning – an illustration*


- Obtain the eigenpairs corresponding to  $[\alpha, \beta]$
- $[\alpha, \beta]$  is divided into 4 sub-intervals
- Use five nodes
- Except for Node #1, each node performs 2 factorizations:
  - one for computing the inertia (blue), and
  - one for the TraceMIN iteration (red).
- Node 1 performs one factorization with shift  $\alpha$



# *A NASTRAN benchmark*

## *Car body dynamics –*

- $A x = \lambda B x$  (order: 1.5 M, and 7.2 M)*
- $A = A^T$ ,  $B := \text{s.p.d.}$*
- $\text{norm}(R, \text{inf}) \leq 10^{-6}$*
- Compute the smallest 1000 eigenpairs using 129 nodes.*



*Sparsity  
Structure  
of  $A$   
 $n \sim 7.2 M$*



*TraceMIN w/ multisectioning*  
*vs. Intel's Math Kernel Library's FEAST*

<i>Problem</i>	<i>size</i>	<i># of smallest <math>\lambda</math>s</i>	<i>TraceMIN (seconds)</i>	<i>FEAST (seconds)</i>	<i>Speed Improve.</i>
<i>Nastran 1</i>	<i>1.5 M</i>	<i>1000</i>	<i>59</i>	<i>121</i>	<i>2.2</i>
<i>Nastran 2</i>	<i>7.2 M</i>	<i>1000</i>	<i>418</i>	<i>Failure</i>	

*All Trilinos eigensolvers failed on this NASTRAN benchmark*

## *TraceMIN w/ multisectioning*

*vs. Intel's Math Kernel Library's FEAST...*

*using 129 nodes;  $\text{norm}(r_k, \text{inf}) / \sigma_k \leq 10^{-5}$*

<i>Problem</i>	<i>size</i>	<i># of <math>\lambda</math>s interval</i>	<i>TraceMIN (seconds)</i>	<i>FEAST (seconds)</i>	<i>Speed Improve.</i>
<i>Anderson*</i>	<i>1.0 M</i>	<i>1143 [-.01,.01]</i>	<i>792</i>	<i>7910</i>	<i>10.0</i>
<i>af_shell10</i>	<i>1.5 M</i>	<i>1045 [2000,2250]</i>	<i>37</i>	<i>274</i>	<i>7.4</i>

- *Anderson Model of Localization (Schrödinger eq.):  $Hx = \lambda x$   
diag (H): random; offdiag(H) = 1*

# *Sampling: computing 400 eigenpairs*

<i>Matrix</i>	<i>Size</i>	<i>Interval</i>	<i>abs. res.</i> $10^{-5}$	<i>abs. res.</i> $10^{-9}$
<i>NASTRAN 1</i>	<i>1.5 M</i>	$[-.01, 10^3]$	<i>21 s</i> <i>~.05 s/ep</i>	<i>40 s</i> <i>~.10 s/ep</i>
<i>NASTRAN 2</i>	<i>7.2 M</i>	$[-.01, 3 * 10^6]$	<i>181 s</i> <i>~.45 s/ep</i>	<i>302 s</i> <i>~.76 s/ep</i>

*Obtain the 4 eigenvalues closest to 100 points uniformly distributed in each interval and the corresponding eigenvectors using TraceMIN on 100 nodes*

*Thank you!*